## Sinker EDM Machines

# Maxicut MX-176 CNC Sinker EDM Machine

### **Features**

#### 10 Orbit Patterns

Reduce the number of electrodes and achieve better surface finishes

#### **Large Program Storage Capacity**

110 programs with up to 8 steps in each

#### **Password Protected Settings**

The program can be password protected to prevent unauthorized changes

#### Auxiliary I/O

Ability to integrate ancillary devices such as rotary tables, indexers, and work piece handling systems

#### **Linear Glass Scales with 1 Micron Resolution**

Provides true, closed loop, position feedback for precise part positioning accuracy

#### FC-35 Grade Casting

High quality cast iron for increased rigidity and work piece capacity

#### **External Data Transfer**

Transfer programs with a USB memory stick or across a network using Ethernet

#### Integrated C Axis (Optional)

Position the electrode automatically, rotate round electrodes at a constant speed, and program synchronized motion for applications such as threads and spirals

#### Automatic Tool Changer - ATC (Optional)

Increase unattended machining by automatically changing electrodes

#### **Adaptive Logic (Optional)**

Difficult applications can be completed with no flushing without the risk of arcing







Serving All of North America ISO 9001: 2015 Registered







# Maxicut MX-176 CNC Sinker EDM Machine Specifications

			MX-176 CNC	
TRAVEL	X AXIS		78.7"	(2,000 mm)
	Y AXIS		27.5"	(700 mm)
	Z AXIS		23.2"	(590 mm)
OPEN HEIGHT *	MINIMUM		26.7"	(680 mm)
	MAXIMUM		50.0"	(1,270 mm)
WORK TABLE	WIDTH		62.9"	(1,600 mm)
	DEPTH		37.4"	(950 mm)
WORK TANK	WIDTH		122.0"	(3,100 mm)
	DEPTH		55.1"	(1,400 mm)
	HEIGHT		24.8"	(630 mm)
	MAXIMUM OIL LEVEL		18.8"	(480 mm)
DIELECTRIC RESERVOIR	CAPACITY		900 gal.	(3,405 liters)
WEIGHT CAPACITY	ELECTRODE ON T SLOT PLATEN		495 lb.	(225 kg.)
	WORK PIECE		14,960 lb.	(6,800 kg.)
GENERATOR	MAXIMUM PEAK CURRENT		200 A	
	ON AND OFF TIME		1 to 4000 μs	
C AXIS **	ELECTRODE WEIGHT CAPACITY	STATIC	88 lb.	(40 kg.)
		DYNAMIC	66 lb.	(30 kg.)
	MAXIMUM PEAK CURRENT	STATIC	100 A	
		DYNAMIC	65 A	
	MAXIMUM ROTATIONAL SPEED		35 RPM	
FLOOR SPACE AND WEIGHT	WIDTH		208"	(528 cm)
	DEPTH		137"	(348 cm)
	HEIGHT		140"	(356 cm)
	MACHINE TOOL WEIGHT		19,400 lb.	(8,800 kg.)
ENVIRONMENTAL	ROOM TEMPERATURE		68 to 77°F	(20 to 25°C)
	RELATIVE HUMIDITY		40% to 55%	
UTILITIES	ELECTRICAL		220VAC ±10%, 60 Hz, 19 KVA	
	AIR		<b>70 PSI @ 1CFM</b> (5 BAR @ 1.7 CMH)	

st Open Height is measured from the T-slot platen to the table. stst Optional.

Illustrations and specifications herein are not binding in detail. Belmont Equipment & Technologies reserves the right to modify and make improvements to these specifications without notice.

