## Sinker EDM Machines

# Maxicut MX-196-D CNC Sinker EDM Machine

### **Features**

#### 10 Orbit Patterns

Reduce the number of electrodes and achieve better surface finishes

#### **Large Program Storage Capacity**

110 programs with up to 8 steps in each

#### **Password Protected Settings**

The program can be password protected to prevent unauthorized changes

#### Auxiliary I/O

Ability to integrate ancillary devices such as rotary tables, indexers, and work piece handling systems

#### **Linear Glass Scales with 1 Micron Resolution**

Provides true, closed loop, position feedback for precise part positioning accuracy

#### FC-35 Grade Casting

High quality cast iron for increased rigidity and work piece capacity

#### **External Data Transfer**

Transfer programs with a USB memory stick or across a network using Ethernet

#### Integrated C Axis (Optional)

Position the electrode automatically, rotate round electrodes at a constant speed, and program synchronized motion for applications such as threads and spirals

#### Automatic Tool Changer - ATC (Optional)

Increase unattended machining by automatically changing electrodes

#### **Adaptive Logic (Optional)**

Difficult applications can be completed with no flushing without the risk of arcing







Serving All of North America ISO 9001: 2015 Registered







# Maxicut MX-196-D CNC Sinker EDM Machine Specifications

				MX-196-D	CNC DUAL HEAD
TRAVEL	X AXIS	EACH HEAD:		88.1"	(2,240 mm)
		TOTAL	ΓRAVEL:	118.1"	(3,000 mm)
	Y AXIS		27.5"	(700 mm)	
	Z AXIS			23.2"	(590 mm)
OPEN HEIGHT *	MINIMUM			26.3"	(670 mm)
	MAXIMUM			49.6"	(1,260 mm)
WORK TABLE	WIDTH			122.0"	(3,100 mm)
	DEPTH			39.3"	(1,000 mm)
WORK TANK	WIDTH			157.4"	(4,000 mm)
	DEPTH			57.0"	(1,450 mm)
	HEIGHT			24.8"	(630 mm)
	MAXIMUM OIL LEVEL			18.8"	(480 mm)
DIELECTRIC RESERVOIR	CAPACITY			1,115 gal.	(4,220 liters)
WEIGHT CAPACITY	ELECTRODE ON T SLOT PLATEN			495 lb.	(225 kg.)
	WORK PIECE			29,920 lb.	(13,600 kg.)
GENERATOR	MAXIMUM PEAK CURRENT			200 A	
	ON AND OFF TIME		1 to 4000 μs		
C AXIS **	ELECTRODE WEIGH CAPACITY	/EIGHT	STATIC	88 lb.	(40 kg.)
			DYNAMIC	66 lb.	(30 kg.)
	MAXIMUM PEAK CURRENT	AK	STATIC	100 A	
			DYNAMIC	65 A	
	MAXIMUM ROTATIONAL SPEED			35 RPM	
FLOOR SPACE AND WEIGHT	WIDTH		305"	(775 cm)	
	DEPTH		190"	(483 cm)	
	HEIGHT			140"	(356 cm)
	MACHINE TOOL WEIGHT			40,810 lb.	(18,550 kg.)
ENVIRONMENTAL	ROOM TEMPERATURE			68 to 77°F	(20 to 25°C)
	RELATIVE HUMIDITY			40% to 55%	
UTILITIES	ELECTRICAL			220VAC ±10%, 60 Hz, 19 KVA	
	AIR			<b>70 PSI @ 1CFM</b> (5 BAR @ 1.7 CMH)	

st Open Height is measured from the T-slot platen to the table. stst Optional.

Illustrations and specifications herein are not binding in detail. Belmont Equipment & Technologies reserves the right to modify and make improvements to these specifications without notice.